



Guardian Pro

VETERINARY MONITOR

Features

- 12.1 inch high resolution color TFT-LCD screen
- Full touch screen and customizable shortcuts for simple and intuitive operation
- No-fan design reduces dust and creates a no noise environment
- Defibrillation and electrosurgical interference protection
- Basic parameters monitoring with optional capnography and anaesthesia monitoring available
- Suitable for feline, canine and other animals




Guardian Pro

12.1" Color TFT-LCD Touch Screen



Guardian Lite

10.4" Color TFT-LCD Touch Screen







No-fan Design



Pitch Tone



Thermal Recorder




Shortcut Menu



Defib Proof & Sync



ESU Proof



VGA Output



Wall Mount




Rolling Stand

Built-in Temporary Memory:




1200

NIBP Measurement Review




120 h

Trend Review



60

Alarm Review



120 s

Frozen Waveform

Standard Parameters

- 3/5-lead ECG, HR, RESP, EDAN SpO₂, EDAN NIBP, PR, 2-TEMP

Optional Parameters

- Nellcor OxiMax™ SpO₂, SunTech NIBP, 2-IBP, EDAN G₂ CO₂ (Sidestream), Respironics CO₂ (Mainstream and Sidestream), Masimo Anesthesia Gas/O₂ (iM70 VET)

Multiple Display Modes




Standard Display



Large Font



Trend View



OxyCRG



Bed to Bed

End Tidal Carbon Dioxide Monitoring



EDAN G₂ CO₂ (Sidestream)

- Superior water trap design for accurate monitoring
- iCARBTM algorithm with intelligent CO₂ pseudo wave identification technology
- Multiple sampling accessories as options

Respironics CO₂ (Mainstream/Sidestream)

- Plug & play module design
- Dehumidification tube instead of water trap
- Low sampling rate of 50ml/min

MASIMO Anesthetic Gas/O₂ (Mainstream/Sidestream)



- Unique plug & play module for mainstream anesthetic gas monitoring
- The no moisture sampling line design suitable for all clinical application
- A stable low flow of 50ml/min